

VELVET Power 1 Spot Studio

Ref.: VP1SPSTNY

Datasheet: November 2024 / Page 1




1x1 foot bicolor dustproof, IP51 AC powered concentrated long distance beam light LED panel

Hard and soft light in the same fixture. Dustproof IP51 bicolor rated panel. Long throw concentrated beam of 15° or 30°. High TLCI & CRI (97). Precise color temperature adjustment from 2700K to 6500K. Totally silent fanless operation. robust and lightweight low-carbon aluminum body. High efficiency: low power consumption. DMX-RDM control. AC & DMX In & Out built-in connectors.

More info

[Website](#)



1. XLR-3 DC In
2. Power switch
3. XLR DMX-5 Out
4. + / - Adjustment buttons
5. 3200K / 5600K Quick access button
6. Mode selection button (Dimmer / Colour Temp)
7. Digital display
8. XLR-5 DMX In

VELVET Power 1 Spot Studio

Ref.: VP1SPSTNY


Datasheet: November 2024 / Page 2




SPECIFICATIONS

COLOUR TEMPERATURE	Adjustable from 2700K a 6500K (100K increments)
LIGHT INTENSITY	Dimmable 0 to 100 (smooth and flicker-free)
LOCAL CONTROL	Shock proof buttons and display
WIRE CONTROL	DMX-RDM with XLR-5 In connector
TLCI INDEX	98 at 3200K and 96 at 5600K
PHOTOMETRICS	6000 lux / 557 fc at 3m / 9.8 feet 1700 lux / 165 fc at 6m/20 feet
BEAM ANGLE	15° Nominal 30° With D25 filter 45° With D50 filter 90° With D100 filter 105° With DVELVET filter
DIMENSIONS	380x308x68mm / 15"x12"x2.7" (panel) 495x395x68mm / 19.5"x15.5"x2.7" (panel+yoke)
WEIGHT	4.2 kg / 9.3 lbs (panel) 4.7 kg / 10.4 lbs (panel + yoke)
POWER DRAW	100 W / 0.91 Amps at 110 VAC
POWER SUPPLY	90-264V AC 50/60Hz through XLR3 connector
LED RATED LIFE	More than 50.000 hours
POWER CONNECTION	Neutrik XLR-3 DC In connector
OUTPUT FREQUENCY	2000 fps
OPERATION TEMPERATURE	From -20°C to +40°C
COOLING	No-noise, fan-free passive cooling
PROTECTION	IP51 dustproof, indoor or outdoor protected use
VELVET LED TECHNOLOGY	Selected BIN High-power LED + VELVET custom optics + CPU software control
CONSTRUCTION & FINISH	Made of black powdercoated extruded and sheet aluminum

VELVET Power 1 IP51 + MO Yoke



VELVET Power 1 IP51 + PO Yoke



VELVET Power 1 Spot Studio

Ref.: VP1SPSTNY

Datasheet: November 2024 / Page 3



PHOTOMETRICS

DIAMETER

∅ 0,8m/ 2.6'

∅ 1,3m/ 4.2'

	15°	28500 lux 2648 fc	9200 lux 855 fc	4300 lux 400 fc	2250 lux 209 fc	1600 lux 149 fc	1200 lux 111 fc	Power 1	
		37000 lux 3437 fc	12800 lux 1189 fc	6000 lux 557 fc	3600 lux 334 fc	2400 lux 223 fc	1700 lux 158 fc	100W	0,40A/220V 0,90A/110V
DISTANCE		1m/ 3.2'	2m/ 6.5'	3m/ 9.8'	4m/ 13'	5m/ 16.4'	6m/ 19.6'	98	96

