ELVET Power 2 Spot Studio

Ref.: VP2SPSTNY

Datasheet: November 2024 / Page 1



2x1 feet bicolor dustproof **AC** powered concentrated long distance beam light LED panel

Hard and soft light in the same fixture. Dustproof IP51 bicolor rated panel. Long throw concentrated beam of 15º or 30º. High TLCI & CRI (97). Precise color temperature adjustment from 2700K to 6500K. Totally silent fanless operation. Robust and lightweight lowcarbon aluminum body. High efficiency: low power consumption. DMX-RDM control. AC & DMX In & Out built-in connectors.



More info







- 1. XLR-3 DC In
- 2. Power switch
- 3. XLR DMX-5 Out
- 4 +/- Adjustment buttons
- 5. 3200K/5600K Quick access button
- 6. Mode selection button (Dimmer/ Colour Temp)
- 7. Digital display
- 8. XLR-5 DMX In



VELVET Power 2 Spot Studio

Ref.: VP2SPSTNY

Datasheet: November 2024 / Page 2




SPECIFICATIONS					
COLOUR TEMPERATURE	Adjustable from 2700K a 6500K (100K increments)				
LIGHT INTENSITY	Dimmable 0 to 100 (smooth and flicker-free)				
LOCAL CONTROL	Shock proof buttons and display				
WIRE CONTROL	DMX-RDM with XLR-5 In connector				
TLCI INDEX	98 at 3200K and 96 at 5600K				
PHOTOMETRICS	8900 lux / 827 fc at 3m / 9.8 feet 2540 lux / 236 fc at 6m/20 feet				
BEAM ANGLE	15° Nominal 30° With D25 filter 45° With D50 filter 90° With D100 filter 105° With DVELVET filter				
DIMENSIONS	690x308x68mm / 27.2"x12"x2.7" (panel) 815x435x68mm / 32.1"x17.1"x2.7" (panel+yoke)				
WEIGHT	7 kg / 15,5 lbs (panel) 7.6 kg / 16.7 lbs (panel + yoke)				
POWER DRAW	190W				
POWER SUPPLY	90-264V AC 50/60Hz through XLR3 connector				
LED RATED LIFE	More than 50.000 hours				
POWER CONNECTION	Neutrik XLR-3 DC In connector				
OUTPUT FREQUENCY	2000 fps				
OPERATION TEMPERATURE	From -20°C to +40°C				
COOLING	No-noise, fan-free passive cooling				
PROTECTION	IP51 dustproof, indoor or outdoor use				
VELVET LED TECHNOLOGY	Selected BIN High-power LED + VELVET custom optics + CPU software control				
CONSTRUCTION & FINISH Made of black powdercoated extruded and sheet aluminum					

VELVET Power 2 IP54+M0 Yoke

815 mm 690 mm 290 mm 515 mm 515 mm

EV-EUR028-T

VELVET Power 2 IP54 + P0 Yoke



VELVET Power 2 Spot Studio

Ref.: VP2SPSTNY

Datasheet: November 2024 / Page 3



PHOTOMETRICS

DIAMETER			7 1,2m/3.9'		2,3m/ 7.5 ¹				
	15°		13000 lux 1208 fc	6400 lux 595 fc	3850 lux 358 fc	2500 lux 232 fc	1780 lux 165 fc		uer 2 0,86A/220V 1,72A/110V
			17000 lux 1579 fc	8900 lux 827 fc	5350 lux 497 fc	3500 lux 325 fc	2540 lux 236 fc	98	96
DIS	STANCE	1m/ 3.2 ¹	2m/ 6.5'	3m/ 9.8'	4m/ 13'	5m/ 16.4'	6m/ 19.6'		

