

VELVET Mini 3 IP54

Ref.: VM3IP54NY

Datasheet: November 2024 / Page 1



3x1/2 feet bicolor weatherproof compact panoramic soft light LED panel

More info

[Website](#)

Natural soft light panel for low ceilings. Rainproof IP54. High TLCI & CRI (96). Precise color temperature adjustment from 2700K to 6500K. Perfect skin tones and real colors. Lightweight, low-carbon aluminum body. Totally silent fanless operation DMX-RDM control. High efficiency means 100% light output even with batteries.



1. Power switch
2. XLR-3 DC In connector
3. Docking plate
4. +/- Adjustment buttons (Dimmer / Colour Temperature)
5. Mode selection button
6. 3200K / 5600K Quick access button
7. Digital display
8. XLR-5 DMX-RDM In connector



VELVET Mini 3 IP54

Ref.: VM3IP54NY


Datasheet: November 2024 / Page 2



SPECIFICATIONS

COLOUR TEMPERATURE	Adjustable from 2700K a 6500K (100K increments)
LIGHT INTENSITY	Dimmable 0 to 100 (smooth and flicker-free)
LOCAL CONTROL	Shock proof buttons and display
WIRE CONTROL	DMX-RDM with XLR-5 In connector (In & Out with DMX splitter)
TLCI INDEX	97 at 3200K and 98 at 5600K
PHOTOMETRICS	3200 lux / 297 fc at 1m / 3 feet 435 lux / 40 fc at 3m / 10 feet
BEAM ANGLE	100°
DIMENSIONS	870 x 190x 90 mm / 34" x 7,5" x 3,5" (panel)
WEIGHT	4,6 kgs / 10 lbs (panel) 5,1 kgs /11,2 lbs (panel + yoke)
POWER DRAW	150W (1.35A at 110 VAC — 0.66A at 220 VAC)
POWER SUPPLY	Vlock or Gold battery quick link mount 90-264 VAC 50/60Hz through Smart AC adapter
LED RATED LIFE	More than 50.000 hours L70 More than 35.000 hours L80
POWER CONNECTION	Neutrik XLR-3 DC In connector
OUTPUT FREQUENCY	2000 fps
OPERATION TEMPERATURE	From -20°C to +40°C
COOLING	No-noise, fan-free passive cooling
PROTECTION	IP54 rainproof, indoor or outdoor use
VELVET LED TECHNOLOGY	Selected BIN LED + optic diffuser + CPU software control
RIGGING OPTIONS	Aluminum yoke with 16mm baby receptacle combined with 28mm junior pin, four sliding threads ¼" for riggings located on panel sides, double baby pin for diagonal or vertical position
QUICK MOUNTING ACCESSORIES	Smart AC power supply (Vlock or Gold available), VELVET DMX remote control, foldable Snapgrid, foldable SnapBag softbox, removable barn doors, cordura case, hard case
CONSTRUCTION & FINISH	Black anodized extruded aluminum and black powder coated sheet aluminum

WIRE VIEW



VELVET Mini 3 IP54

Ref.: VM3IP54NY

Datasheet: November 2024 / Page 3



PHOTOMETRICS

DIAMETER

∅ 4,8/ 15.7'

∅ 8m/ 26.2'

